



DRY CLEANING FLUIDS

Sales Specification
Rev. 5 (08/00)

DF-2000 Ô Fluid

Properties	Test Methods	Sales Specifications
Appearance	Visual	Pass
Aromatics Content, wt. %	AM-S 140.31	0.02 max
Bulk Odor	BTQAL – 018	Pass
Color, Saybolt Units	ASTM D 156	30 min
Flash Point, °C	ASTM D 56	60 min
Specific Gravity @ 15.6/15.6°C	ASTM D 4052	0.760 – 0.775

*** This product contains approximately 7 ppm BHT as added to the manufacturing site certified storage tank.**

DF-2000 is a trademark of Exxon Mobil Corporation. Imperial Oil is a licensee.

For more information, to request samples and/or to place orders, call: 1 (800) 663-4109

The user may forward, distribute, and/or photocopy this copyrighted document only if it is unaltered and complete. You may not copy this document to a Web site. This information relates only to the material designated and may not be valid for such material used in combination with any other materials or in any process. Typical values are representative of production, may vary over time and may not match the date of publication. All information, to the best of our knowledge and belief, is accurate and reliable as of the date compiled. Moreover, no warranty or guarantee is made as to its accuracy, reliability or completeness nor do we offer any warranty against patent infringement. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. Sampling and testing procedures in effect at the time of production will be used for certification testing. Results may be based on tank certification, manufacturing data, periodic testing, compliance testing, shipment, end of run, rundown tank or most recent restock analysis. We reserve the right to use other test methods in certifying this material.