



ExxonMobil^ä IPA

Oxygenated Fluid
Isopropyl Alcohol Anhydrous

Rev. 1, 10/2005

Global Sales Specification

Properties	Test Methods	Units	Lower Values	Upper Values
Acidity, as acetic acid	ASTM D 1613	wt%		0.001 max.
Color, Platinum Cobalt Scale	ASTM D 1209	Pt-Co Scale		5 max.
Non-Volatile Matter	ASTM D 1353	g/100ml		0.001 max.
Purity by GC	DIN 55685	wt%	99.8 min.	
Specific Gravity 20/20°C	ASTM D 4052	-	0.7862 min.	0.7870 max.
Water Content	ASTM D 1364	wt%		0.1 max.
Water Miscibility	ASTM D 1722	Visual	Clear & Miscible	

Properties	Test Methods	Units	Range includes	Max Range
Distillation Range	ASTM D 1078	°C	82.3	1.0 max.

Notes:

ExxonMobil[™] IPA meets:

U.S. Federal Specification TT-I-735A Amendment 3, Notice 2, 19 April 2001 Grades A and B

ASTM Specification D 770-05

For more information, to request samples and/or to place orders, call: 1 (800) 663-4109

The user may forward, distribute, and/or photocopy this copyrighted document only if it is unaltered and complete. You may not copy this document to a Web site. This information relates only to the material designated and may not be valid for such material used in combination with any other materials or in any process. Typical values are representative of production, may vary over time and may not match the date of publication. All information, to the best of our knowledge and belief, is accurate and reliable as of the date compiled. Moreover, no warranty or guarantee is made as to its accuracy, reliability or completeness nor do we offer any warranty against patent infringement. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. Sampling and testing procedures in effect at the time of production will be used for certification testing. Results may be based on tank certification, manufacturing data, periodic testing, compliance testing, shipment, end of run, rundown tank or most recent restock analysis. We reserve the right to use other test methods in certifying this material.