



# HYDROCARBON FLUIDS

Sales Specification  
Rev. 15 (12/ 2010)

## ESCAID™ 110 Fluid

Properties	Test Methods	Sales Specifications
Aniline Point, °C	ASTM D 611	65.6 min
Appearance	Visual	Pass
Aromatics Content, wt. %	AM-S 140.31	0.5 max
Color, Saybolt Units	ASTM D 156 or ASTM D 6045	30 min
Distillation	ASTM D 86	
IBP, °C		192 min
DP, °C		250 max
Flash Point, °C	ASTM D 93	70 min
Pour Point, °C	ASTM D 97	-35 max
Specific Gravity @ 15.6/15.6°C	ASTM D 4052	0.790 – 0.810
Viscosity @ 40°C, cSt	ASTM D 445	1.50 – 1.75

ESCAID is a trademark of Exxon Mobil Corporation. Imperial Oil is a licensee.

For more information, to request samples and/or to place orders, call: 1 (800) 663-4109

The user may forward, distribute, and/or photocopy this copyrighted document only if it is unaltered and complete. You may not copy this document to a Web site. This information relates only to the material designated and may not be valid for such material used in combination with any other materials or in any process. Typical values are representative of production, may vary over time and may not match the date of publication. All information, to the best of our knowledge and belief, is accurate and reliable as of the date compiled. Moreover, no warranty or guarantee is made as to its accuracy, reliability or completeness nor do we offer any warranty against patent infringement. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. Sampling and testing procedures in effect at the time of production will be used for certification testing. Results may be based on tank certification, manufacturing data, periodic testing, compliance testing, shipment, end of run, rundown tank or most recent restock analysis. We reserve the right to use other test methods in certifying this material.