



# ISOPARAFFINS

Sales Specification  
Valid: 9/2010

## ISOPAR™ M Solvent

Properties	Sales Specifications		Test Methods
	Minimum	Maximum	
Aniline Point, °C	87	96	ASTM D611 Modified
Appearance	Bright and Clear (B&C)		ASTM D4176 Modified
Aromatic Content, wt.%		0.05	UV Spectroscopy
Colour, Saybolt	+30		ASTM D156 Modified
Distillation, °C			ASTM D 86 Modified
IBP	218		
Dry Point		257	
Flash Point, °C (Pensky Martens Closed Cup)	93.5		ASTM D93 Modified
Specific Gravity, 15.6/15.6°C	0.784	0.796	ASTM D1250 Modified
Sulphur, wppm		1	ASTM D5623 Modified
Viscosity @ 40°C, cSt	2.2	3.1	ASTM D445

**ISOPAR™ M Solvent contains approximately 10 ppm BHT as added to the manufacturing site certified storage tank.**

**This product has been evaluated by ExxonMobil Chemical and meets the low vapor pressure (LVP) exemption set by the California Air Resources Board for volatile organic compounds in consumer products (California Code of Regulations, Title 17, Article 2, Section 94510).**

ISOPAR is a trademark of Exxon Mobil Corporation. Imperial Oil is a licensee.

For more information, to request samples and/or to place orders, call: 1 (800) 663-4109

The user may forward, distribute, and/or photocopy this copyrighted document only if it is unaltered and complete. You may not copy this document to a Web site. This information relates only to the material designated and may not be valid for such material used in combination with any other materials or in any process. Typical values are representative of production, may vary over time and may not match the date of publication. All information, to the best of our knowledge and belief, is accurate and reliable as of the date compiled. Moreover, no warranty or guarantee is made as to its accuracy, reliability or completeness nor do we offer any warranty against patent infringement. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. Sampling and testing procedures in effect at the time of production will be used for certification testing. Results may be based on tank certification, manufacturing data, periodic testing, compliance testing, shipment, end of run, rundown tank or most recent restock analysis. We reserve the right to use other test methods in certifying this material.