

Mobil Super ATF+4®

Automatic Transmission Fluid

Product Description

Mobil Super ATF+4®, is a synthetic blend ATF and used as makeup or full fill, is specially formulated to ensure optimal performance in Chrysler transmissions and transaxles. Its unique additive package provides the proper frictional properties, excellent low-temperature fluidity and dependable wear protection required in applications where a Chrysler MS-9602 or MS 7176 type fluid is recommended

Features and Benefits

The outstanding performance features of Mobil Super ATF+4® offer the following advantages over ATF+3®:

- Improved flow properties at low start-up temperatures and high operating temperatures
- Improved shift performance and vehicle driveability/improved shudder performance in Chrysler vehicles
- Excellent viscosity stability
- Excellent oxidation stability, less fluid breakdown in high-temperature service
- Excellent protection against rust and corrosion
- Provides more assured wear protection for maximum transmission/transaxle life
- Recommended Drain Interval of 160,000 km

Applications

Mobil Super ATF+4® is an automatic transmission/transaxle fluid specially formulated for Chrysler Corporation vehicles, including Chrysler, Dodge, Plymouth, Eagle and certain Jeeps, that require a fluid meeting Chrysler specification MS-9602 and earlier Chrysler specifications. It is also recommended for Mitsubishi and Hyundai applications where an MS-9602 or MS-7176 type fluid is specified.

Mobil Super ATF+4® is not recommended for vehicles that require Ford Mercon® or General Motors Dexron® type fluids. For these applications, Mobil Multi-Vehicle ATF is recommended.

Mobil Super ATF+4® can be used in other services that specify an MS-7176E® type fluid, including certain manual transmissions, transfer cases and power steering units.

Note: Use of fluids that do not meet the MS-9602 specification can impair performance, causing transmission shudder, rough shifting and unsatisfactory vehicle driveability. Use of non-approved fluids also may invalidate new vehicle warranties.

Due to continual product research and development, the information contained herein is subject to changes without notification. Additional important health and safety information on this product can be found in the Material Safety Data Sheet, which is available online at www.imperialoil.ca/mobil or by contacting Lubricants and Petroleum Specialties, Technical Services, Technical Help Desk: 1-800-268-3183

© 2001 Imperial Oil
© The Mobil logotype and the Pegasus design are registered trademarks of Exxon Mobil Corporation.
™ Trademark of Exxon Mobil Corporation, Imperial Oil, Licensee.



Automatic transmissions should be checked for proper fluid levels at regular intervals, and the fluid should be changed at manufacturer-recommended intervals. However, this may vary due to your vehicle's operating conditions. Some manufacturers recommend more frequent changes of transmission fluid under severe driving conditions, such as heavy traffic, hot weather and trailer pulling.

Specifications and Approvals

Mobil Super ATF+4®	
Chrysler MS-9602	X

Typical Properties

Mobil Super ATF+4®	
Viscosity	
cSt @ 40°C	34.4
cSt @ 100°C	7.5
cP @ -40°C	8,800
Viscosity Index	200
Flash Point, °C	180
Pour Point, °C	-50
Density	0.8511
Color	Red

Precautions

Mobil Super ATF+4® is manufactured from a blend of high quality synthetic and conventional base stocks, carefully blended with selected additives. As with all petroleum products, good personal hygiene and careful handling should always be practiced. Avoid prolonged contact to skin, splashing into the eyes, ingestion or vapour inhalation. Special care is also recommended in handling used motor oils. A Service Data Sheet entitled "Safe Handling of Used Motor Oils" is available on request from your Imperial Oil Representative. Please refer to our Imperial Oil Material Safety Data Sheet for further information.

Note: This product is not controlled under Canadian WHMIS legislation.

The Mobil logotype, the Pegasus design and Mobil Super are trademarks of Exxon Mobil Corporation, or one of its subsidiaries ATF+4® and ATF+3® are registered trademarks of Chrysler LLC.

8-2008

Due to continual product research and development, the information contained herein is subject to changes without notification. Additional important health and safety information on this product can be found in the Material Safety Data Sheet, which is available online at www.imperialoil.ca/mobil or by contacting Lubricants and Petroleum Specialties, Technical Services, Technical Help Desk: 1-800-268-3183

© 2001 Imperial Oil
® The Mobil logotype and the Pegasus design are registered trademarks of Exxon Mobil Corporation.
™ Trademark of Exxon Mobil Corporation, Imperial Oil, Licensee.

