

# Mobil Delvac Xtreme Grease

## Extended Service Automotive/Heavy Equipment Grease

### Description

Mobil Delvac Xtreme Service Grease is a high performance, heavy duty truck and heavy equipment grease having excellent extreme-pressure and anti-wear properties. It contains a high viscosity base oil and a lithium complex thickener to provide extended service, water spray-off resistance, and heavy duty, extended service. The lithium soap, combined with an advanced additive system, delivers outstanding high-temperature performance properties.

It is designed to provide regreasing intervals comparable to crankcase extended drain intervals.

### Application

Mobil Delvac Xtreme Service Grease is recommended for the lubrication of heavy duty and extended service automotive and off-highway mobile equipment. It is also an excellent fifth wheel lubricant. This grease sheds water, continues to lubricate and aids in forming a strong water and dirt resistant seal for excellent lubrication protection in tough extended service applications. Even in the presence of water, the grease maintains its consistency and protects against corrosive wear. Its extreme-pressure properties and high oil viscosity reduce wear, making it especially applicable for heavy shock loads.

As this grease is designed for extended service applications with very infrequent re-applications, it is also recommended that all grease pumping and application equipment be checked by a qualified Mobil service representative to ensure its serviceability.

It will pump well with standard equipment, but low air pressures, incorrect or worn pumping equipment, or very long inadequately sized lines can cause inadequate grease applications.

### Advantages

Mobil Delvac Xtreme Service Grease provides the following performance advantages and benefits.

- Excellent resistance to wear
- Fewer pin and other component failures caused by water and dirt contamination
- Lower maintenance costs
- Good pumpability at moderate temperatures
- Better stay-put properties at high temperatures, high loads and tough service
- Extended service capabilities

### Typical Properties

<b>Mobil Delvac Xtreme Grease</b>	
NL GI Grade	2
Soap Type	Lithium Complex
Structure	Smooth/ Very Tacky
Color	Orange
Penetration	265-295
Dropping Point	500°F
Oil viscosity, cSt at 40°C	288-352
cSt at 100°C	25
SUS at 100°F	1700
SUS at 210°F	125
ISO VG	320
Timken OK load, lbs	40
Four-Ball EP Test, Weld Load, KG, Min.	250
Load Wear Index	45
Four -Ball Wear, Scar Diam, mm	0.4
Rust Test,	Pass
USS Mobility, USS DM 43, 0°F, g/min	2.0



## Precautions

Mobil Delvac Xtreme Service Grease is manufactured from high quality petroleum base stocks, carefully blended with selected soaps and additives. As with all petroleum products, good personal hygiene and careful handling should always be practiced. Avoid prolonged contact to skin, splashing into the eyes, ingestion or vapour inhalation. High-pressure injection of any grease under the skin can cause serious delayed soft tissue damage and should be treated immediately by a physician. To avoid injection injuries, inspect greasing equipment regularly for worn hoses and fittings. Keep finger away from the nozzle and ensure the nozzle is firmly in place before discharging the grease. Please refer to our Imperial Oil Material Safety Data Sheet for further information.

Note: This product is not controlled under Canadian WHMIS legislation.

Due to continual product research and development, the information contained herein is subject to changes without notification. Additional important health and safety information on this product can be found in the Material Safety Data Sheet, which is available online at [www.imperialoil.ca/mobil](http://www.imperialoil.ca/mobil) or by contacting Lubricants and Petroleum Specialities, Technical Services, Technical Help Desk: 1-800-268-3183

© 2001 Imperial Oil  
® The Mobil logotype and the Pegasus design are registered trademarks of Exxon Mobil Corporation.

Oct-01