

Mobil Super 2000

High Mileage Motor Oil

Product Description

Mobil Super 2000 uses a combination of synthetic and conventional high quality base oils combined with modern performance additives to help provide long engine life and outstanding protection for vehicles with more than 120,000 kilometres. Formulated with seal conditioner, Mobil Super 2000 helps prevent leaks and reduce oil consumption.

These oils protect against sludge, engine rust and corrosion under severe and low-temperature operating conditions. Pour point depressants and a viscosity index (VI) improver are included to provide the optimum viscosity and fluidity across a broad range of temperatures.

Mobil Super 2000 oils are available in three multi-viscosity grades: SAE 5W-20, 5W-30 and 10W-30.

Mobil Super 2000 5W-20, 5W-30 and 10W-30 contain friction-reducing additives. All three products meet or exceed ILSAC GF-5 and API SN and are backward compatible with earlier performance levels such as API SM, SL, and SJ. The American Petroleum Institute (API) classifies these three products as "Resource Conserving" engine lubricants.

Features and Benefits

- Helps extend engine life
- Contains seal conditioner to help prevent or control leaks and reduce oil consumption
- Protects older engines
- Extended performance, guaranteed protection to 10,000 kilometres oil drain interval**
- Outstanding wear protection under a wide variety of operating conditions
- Easy cold starting.
- Meets or exceeds the latest industry specifications
- Satisfies the latest fuel efficiency requirements

***The extended performance and guaranteed protection applies to vehicles recommending oil drain intervals 10,000 km or less. Excludes severe service applications involving: racing and commercial use; frequent towing or hauling; extremely dusty or dirty conditions; or excessive idling. While under warranty change oil at the manufacturer's recommended interval.*

Applications

- Mobil Super 2000 5W-20, 5W-30 and 10W-30 are recommended for higher mileage (generally more than 120,000 kilometres) gasoline, propane or E-85 fueled cars and light duty trucks requiring an API SN, SM, SL or SJ product. They also meet the requirements of ILSAC GF-5 (Starburst Certification Symbol).
- Before using a Mobil Super 2000 motor oils, consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and API Service Classification.



Specifications and Approvals

Mobil Super 2000 meets or exceeds the requirements of:

	5W-20	5W-30	10W-30
API SN	X	X	X
API SM	X	X	X
API SL	X	X	X
API SJ	X	X	X
ILSAC GF-5	X	X	X
Ford WSS-M2C945-A	X		
Ford WSS-M2C930-A	X		
Ford WSS-M2C946-A		X	
Ford WSS-M2C929-A		X	

Typical Properties

Mobil Super 2000	5W-20	5W-30	10W-30
API Service Classification	SN	SN	SN
Specific Gravity	0.859	0.859	0.867
Pour Point, °C	-33	-33	-33
Flash Point, °C (°F), ASTM D 92	241	224	220
Viscosity			
cSt at 40°C	49	61	66
cSt at 100°C	8.5	10.4	10.4
CCS, cP	5,530@ - 30°C	5,500@ - 30°C	4,900@ - 25°C
MRV, cP	23,200@ - 35°C	25,900@ - 35°C	14,300@ - 30°C
Viscosity Index	153	159	145
Resource Conserving	Yes	Yes	Yes

Precautions

The products described on this data sheet are manufactured from high quality petroleum base stocks, carefully blended with selected additives. As with all petroleum products, good personal hygiene and careful handling should always be practiced. Avoid prolonged contact to skin, splashing into the eyes, ingestion or vapour inhalation. Please refer to the Material Safety Data Sheet for further information.

Note: The products described on this data sheet are NOT controlled under Canadian WHMIS legislation.

Mobil Super is a trademark of ExxonMobil Corporation, or one of its subsidiaries. Imperial Oil, Licensee.

10-2010